Project Name:				
Project Address:		Date:		
Designer of Record:	Telephone: Telephone:			
Contact Person:				
City:				
 Load calculations have been provided for sizing of systems and equipment (§ 7.4.1). Equipment efficiencies meet or exceed the requirements of Table 7.8 (§ 7.4.2). Circulating systems are fully insulated (per Table 6.8.3) and have automatic pump controls (§ 7.4.3 and § 7.4.4.2). Non-circulating systems have insulated heat traps and outlet piping insulated (per Table 6.8.3) for 8 ft from the storage tank (§ 7.4.6) 	 Mandatory Provisions Checklist □ Tanks with remote heaters have circulation pump controls (§ 7.4.4.4). □ All water-heating systems have temperature controls that are adjustable down to 120°F or lower (§ 7.4.4.1). □ Systems designed with pipe heating systems such as heat trace have temperature or time controls (§ 7.4.4.2). 	 □ Public lavatories have outlet temperature controls that limit the discharge temperature to 110°F (§ 7.4.4.3). □ Pool heaters have readily accessible control and gas-fired heaters do not have standing pilot lights (§ 7.4.5.1). □ Heated swimming pools have vapor retardar covers (§ 7.4.5.2). □ Pool heaters and circulation pumps have tim switches (§ 7.4.5.3). 		

System Tag	Equipment Type (From Table 7.8)	Sub-Category or Rating Condition (From Table 7.8)	Input Rating (Btu/h or kW)	Volume (gal)	Energy Factor or Et		Standby	Loss
					Rated	\geq Required	Rated	\geq Required
						≥		≥
						≥		≥
						≥		≥
						≥		≥

Combination Space and Water Heating Worksheet (§ 7.5.1)

System Tag	Standby Loss	Standby Loss Method		or Energy Use Exception (attach calculations		or Size Exception		
	Equipment	≥	Requirement	Equipment	≥	Requirement	Equipment	≥ Requirement
		≥			≥			≥ 150,000 Btu/h
		≥			≥			≥ 150,000 Btu/h
		≥			≥			≥ 150,000 Btu/h
		≥			≥			≥ 150,000 Btu/h

